

Job No.	Job Name	Quantity
Adapters	Adapters	
Adapter3.5"	Adapter 3.5" Reg API box - 3 1/2" reg API Pin	3
Adapter 4.5"	Adapter 4.5" API Reg Box to 3.5 inch API reg Rin	1
Blower Tubes	Blower Tubes	
Blower Tube 5"	Blower Tube for 5" Hammer QL50	4
Blower Tube 6"	Blower Tube for 6" Hammer QL60	2
Blower Tube 8"	Blower Tube for 8" Hammer QL80	2
Camera	Underground Camera UDM200 73mm Dual 200m with manual winch Depth - 200m Depth Gauge 200m Steel	1
		1
Casing Clamps	Casing Clamps	
Casing Lifter	Casing Lister	1
Chain Grip	Casing Clamp Chain Grip type	3
Wedge type 178	Wedge type casing clamp 178mm	1
Wedge Type 219	Wedge type casing clamp 219mm	1
Casing Extractor	Casing Extractor	
Casing Extract	Casing Extractor - Drill Bit 10" (254mm) Button Bit (QL80)	1
Compressor	Atlas Copco XRV1200 cfm 23 bar (mechanical) Serial no: PNE951086	1
	Air hose 2 inch	1
	High heat air hose with 2 inch hose tails and high pressure clamps	
Drill Bits	Drill Bits	
Drag Bit 10"	Drag Bit/ clay cutter 10" (3.5" API)	1
Drag Bit 8"	Drag Bit/ clay cutter 8.5" (3.5" API)	1
IBit 5.5"	Drill Bit 5.5" QL50)	1
Drill Bit 6.5"	Drill Bit 6.5" (165mm) Button Bit (QL60)	3
Drill Bit 8"	Drill Bit 8" QL60	1
Drill Bit 8.5"	Drill Bit 8.5" button Bit (QL60)	1
Drill Rods	Drill Rods	
	Drill Rod 3M - 114mm Sch40 3 1/2" API reg	50
	Drill Rod 2M - 114mm Sch80 - 3 1/2" API reg	2
Drilling Equipment	Drilling Equipment	
Bit Grinder & C	Air operated Bit Grinder	1
Chain Tong	Chain Tong H/D for 4-8" hammer	1
Diverter Box:	Diverter Box: Included: 3 x extra rubber seals for 114mm drill rods 3 x extra rubber seals on 168mm casing 3 x extra rubber seals on 219mm casing 1 x adapter for 219mm casing 1 x adapter for 168mm casing Cam lock extension pipe 7 meter	1
Drill Bit Lock	Drill Bit Lock Plate	3

Generator	Generator Honda Generator	1
Mig Welder	Lincoln 3 in 1 Mig Welder	1
Pipe Cutting Machine	Pipe cutting machine with 2.4m chain comet	1
Submersible Pump	BBC S4M 30-420 sub pump, control box, seal, cable connector and 2.5mtrs of cable	1
Hammer Spares	Hammer Spares	
Chuck Nut 5"	Chuck Nut for 5" hammer QL50	4
Chuck Nut 6"	Chuck Nut for 6" hammer QL60	2
Chuck Nut 8"	Chuck Nut for 8" hammer QL80	1
Hammers	Hammers	
Hammer 5" QL50	Hammer 5" QL50	3
Hammer 6" QL60	Hammer 6" QL60 3.5 inch API reg pin	2
Hammer 8" QL80	Hammer 8" QL80 3.5inch API reg pin	1
Odex Equipment	Odex Equipment	
Drill Bit Odex	Drill Bit Odex 178mm QL50	3
Odex Bit 219mm	Odex Bit for 219mm casing QL60	2
Odex Shoe 168mm	Odex Shoe for 168mm casing	6
Odex Shoe 219mm	Odex Shoe for 219mm casing	5
Spares	Spares	
Hose Tail End	Hose Tail End	0
Male Spud	Male Spud	0
Rod Wiper Seals	Rod Wiper Seals	0
Rotary Head SIE	Rotary Head Wear Sleeve	3
Stainless S Grid	Stainless S Grid	0
V-Pack Seal B80	V-Pack Seal B80 (Chevron) Seal	3
Vehicles	Vehicles	
61S96 Tandem Trailer	10x5 Tandem Trailer with cage	1
90C72 Rig	Trailer Drilling Rig Specifications: Drill rig with a rated depth capacity of 300 meters Axles - 2 x 5 ton air braked axles Weight 5.4 ton Feed cylinder - 100mm barrel, 70mm shaft, 4 meter stroke Outrigger (jacks) - 4 x boxed outriggers with 800 meter stroke Foam pump - 21 litre per min 35 bar Foam/water tank - 120 litre Tower - direct on cylinder. Triangle shape. Winch - 1 ton Push down force - 5 000 kgf @ 175 bar Pull up force - 13 000 kgf @ 175 bar Tilt cylinders - 2 x 80 barrel 50 shaft Breakout - cylinder 300mm stroke Hydraulic oil cooler Hydraulic oil tank capacity 330 litres Engine - F6L912 66 kw at sea level Extended tower to accommodate a 4 meter stroke cylinder Spanners included: 1 - breakout 2 - Keeper 3 -Hammer Modification: Hydraulically tilt rotary head Modification rotary changed to: Geared rotary head with hollow spindle (8000 Nm torque)	1